



## u8|GOV TERMINAL

### MAKING MOBILE GLOBAL

The Kymeta™ u8 GOV hybrid terminal provides a complete connectivity solution for communications-on-the-move (COTM) and networks-on-the-move (NOTM) when and where you need it most. The u8 GOV hybrid terminal, with Kymeta revolutionary software-defined, electronic beam-steering technology, is low profile and easy-to-mount on vehicles and vessels.

The u8 GOV terminal is easily transportable and can support communication while in the case, on the ground, or mounted on a vehicle for easy deployment in multiple use cases. The multi-function hardened case is tested to MIL-STD-810H transportation standards and comes with hardened tie down points.

Kymeta u8 GOV hybrid terminals and u8 GOV hybrid terminals integrate the iDirect 950mp router and support external modems such as Viasat CBM400 and most commercial modems.

Broadband by-the-gigabyte connectivity packages are available from Kymeta in either MIR or MIR/CIR plans. TRANSEC services are also available. Kymeta Connect™, an all-inclusive bundle of hardware, connectivity, and support, is offered at an affordable monthly rate.



#### TURNKEY SOLUTIONS

MULTIPLE TERMINAL CONFIGURATIONS PROVIDE THE HARDWARE, SOFTWARE, AND CONNECTIVITY YOU NEED.



#### DESIGNED FOR MOBILE PLATFORMS

LOW PROFILE, AERODYNAMIC DESIGN, NATIVE DC POWER INPUT, AND NEW ACCESSORIES SIMPLIFY VEHICLE INTEGRATION.



#### EXTENDED ENVIRONMENTAL COVERAGE

WITH AN ALL-OUTDOORS CONSTRUCTION AND IP66 RATING, THE u8 GOV TERMINAL IS DESIGNED FOR THE MOST DEMANDING ENVIRONMENTS.



#### PORTABLE AND RUGGED

WITH A HARDENED REUSABLE SHIPPING CASE, THE KYMETA u8 GOV TERMINAL PROVIDES THE FASTEST OUT-OF-THE-BOX COMMUNICATION ANYWHERE—JUST ADD POWER.



#### LEO-UPGRADEABLE

THE u8 ANTENNA ANTICIPATES THE ARRIVAL OF Ku-BAND LEO CONSTELLATIONS. YOUR TERMINAL CAN BE UPGRADED TO A LEO CONFIGURATION AT A LATER TIME.



# u8 GOV Hybrid Terminal Specifications\*

## CONNECTIVITY

### SETUP TIME OF TERMINAL

Unpackage, lift, mount, and operate in less than 20 minutes

### ACQUISITION OF SIGNAL

Less than 1 minute from initiation of acquisition

### SATCOM MODEM

Integrated iDirect 950mp satellite router

## MECHANICAL

### DIMENSIONS

#### TERMINAL CONFIGURATIONS:

L 89.5 cm × W 89.5 cm × H 14 cm  
L 35.2 in. × W 35.2 in. × H 5.5 in.

#### GO CONFIGURATIONS:

L 104 cm × W 104 cm × H 38 cm  
L 41 in. × W 41 in. × H 15 in.

### WEIGHT

#### TERMINAL CONFIGURATIONS:

34 kg (75 lb.)

#### GO CONFIGURATIONS:

~68 kg (~150 lb.)\*\*\*

### OPERATIONAL TEMPERATURE

-40 °C to +55 °C (ambient)

-40 °C to +70 °C (with solar load)

### STORAGE TEMPERATURE

-40 °C to +85 °C

### INGRESS PROTECTION

IP66

## POWER

### DC INPUT POWER

12 VDC to 36 VDC max

### POWER CONSUMPTION

#### (WITH INTEGRATED MODEM)

130 W (typical), 250 W (peak)\*\*

## INTERFACES

### NETWORK INTERFACE

Ethernet

## ANTENNA

### BAND

Ku

### ANTENNA TYPE

Electronically scanned array

### POLARIZATION

Linear, software-defined

### RX FREQUENCY RANGE

10.7 GHz to 12.75 GHz

### G/T BROADSIDE

9.5 dB/K to 12 dB/K

### RX INSTANTANEOUS

#### BANDWIDTH

250 MHz

### TX FREQUENCY RANGE

13.75 GHz to 14.5 GHz

### EIRP BROADSIDE

46 dBW to 46.5 dBW

## TRACKING

### SCAN ANGLES

Az 360°, El +15° to +90°

### TRACKING RECEIVER TYPE

Integrated tracking system

DVB-S2, DVB-S2X

## COMPLIANCE

### CERTIFICATIONS

CE, FCC, Nemko, WEEE, RoHS

## AVAILABLE GOV CONFIGURATIONS

### u8 GOV HYBRID TERMINAL

- u8 antenna with integrated ACU and power supply
- iDirect 950mp satellite modem (global or North America and public safety configurations)
- Embedded LTE Advanced Pro modem card
- RF chain with low-profile BUC
- Shroud

### U8 GO GOV HYBRID TERMINAL

- u8 GOV hybrid terminal
- AC-to-DC universal power kit
- External hardshell case
- Vehicle mount

## AVAILABLE ACCESSORIES

- Vehicle mount kit
- Vehicle power kit
- AC-to-DC power kit
- Adapter plate for existing u7 mounts
- Cables

## AVAILABLE SOFTWARE-ENABLED FEATURES

- Manual positioning (GPS denied) mode
- Full privacy mode
- External GPS support

## KYMETA | CONNECT™

Kymeta Connect™ offers full-service connectivity solutions for u8 terminals. By-the-gigabyte packages are available with either satellite or hybrid satellite/cellular capacity. TRANSEC services are also available for the u8 GOV and u8 GO GOV hybrid terminals. Refer to the Kymeta Broadband product sheet (700-00114-000) for more detail.

\*Specifications as of 26 August 2021. Subject to change.

\*\*Software-controlled peak power draw. User-configurable to a higher threshold for very low-temperature operation.

\*\*\*The exact weight depends on the u8 GO product configuration.



**u8** | GO

For more information, contact Kymeta at [sales@kymetacorp.com](mailto:sales@kymetacorp.com).

12277 134th Ct. NE, Redmond, WA 98052 | Phone: 425.896.3700 | [www.kymetacorp.com](http://www.kymetacorp.com)

© 2021 Kymeta Corporation. KYMETA and KYMETA CONNECT are trademarks of Kymeta Corporation, with registrations or pending applications for these marks in the U.S. and other countries. All other trademarks are the property of their respective owners.

**KYMETA™**

700-00112-000 rev K