



YOUR ONLY BROADBAND CONNECTIVITY SOLUTION FOR ON-THE-GO COMMUNICATIONS WHEN AND WHERE YOU NEED IT IN A SINGLE INTEGRATED PLATFORM



KEY FEATURES

allation Enterprise

Easy installation Native mobility support

Low profile and light weight Low power (~100 W nominal)

Hybrid cellular / Wi-Fi optional

wer (~100 vv norminal) Commercial

Single RX/TX aperture in full duplex

First Responders

Commercial Fishing

MARKETS

Transportation

Recreational Maritime

Industrial Comms on the Move





	\//	
TERMINAL CONFIGURATION	HAWK u8 GEO ODU	HAWK u8 GEO TERMINAL
Antenna type	Full duplex, single aperture, Ku-band flat-panel antenna, electronically steered holographic beamforming array	
Scan angles	Azimuth: 360°, Elevation: +15° to +90°	
Polarization	Linear, software-defined (circular capable)	
Receive (RX) band	10.70 GHz to 12.75 GHz	
RX performance	G/T (broadside) 9 dB/K to 12 dB/K	
Transmit (TX) band	13.75 GHz to 14.50 GHz	
TX performance	EIRP (broadside) 45.5 dBW to 46.5 dBW	
Cross-pol isolation	≥25 dB (typical)	
Satellite modem	N/A	Embedded iDirect iQ 200
Interfaces	Ethernet	
Dimensions	L 89.5 cm × W 89.5 cm × H 14 cm / L 35.2 in. × W 35.2 in. × H 5.5 in.	
Weight	30.8 kg / 68 lb.	30.4 kg / 67 lb.
Input power**	12 VDC to 36 VDC	
Power (typical, steady state)***	85 W	100 W
Operational temperature	-40 °C to +55 °C (ambient) / -40 °C to +70 °C (with solar load)	
Storage temperature	-40 °C to +85 °C	
Ingress protection	IP66	
Compliance	CE, FCC, Nemko, WEEE, RoHS	

GO CONFIGURATION

- » Hawk u8 GEO or GEO-LTE terminal
- » Rugged transport case with built-in tie-down points and support for rapid water ingress
- » Tilt mechanism for COTP deployments
- » AC-to-DC universal power kit
- » Vehicle mount



GEO-LTE TERMINAL CONFIGURATION

Hawk u8 GEO terminal with:

- » Embedded 600 Mbps (CAT 12) cellular modem
- » Ethernet & Wi-Fi (802.11 b/g/n) interfaces
- » 130 W typical, steady-state power
- » Product weight: 31.8 kg / 70 lb.

AVAILABLE ACCESSORIES

- » Vehicle mount kit
- » Vehicle power kit
- » AC-to-DC power kit

KYMETA

B R O A D B A N D

Kymeta offers full-service connectivity solution for the u8 product family. Gigabyte packages are available with either satellite or hybrid satellite/cellular services.



^{**}AC input support available via accessory.















For more information, contact Kymeta at sales@kymetacorp.com

12277 134th Ct. NE, Redmond, WA 98052, USA | Phone: +1.425.896.3700 | www.kymetacorp.com



^{***}Software-controlled peak power draw. User-configurable to a higher threshold for very low-temperature operation.